

Bolin Technology FEX30BHD-NP2 HD Fixed IP Zoom Camera with 30X Optical Zoom

Camera

Image Sensor	1/2.8 inch CMOS 2MP
Lens	30X, 4.5~135mm
Horizontal Angle of View	61.1°(W)~4.3°(T)
Min. Illumination	0.025lux(F1.6, AGC ON, Color), 0.0025lux(F1.6, AGC ON, B/W)
WDR	YES, 120db
Day/Night	YES
Privacy Zone Masking	YES
Defog	YES

Resolution/Frame Rate

IP Output-4K	12MP(4000X3000)20; 8MP(3840X2160)30/25; 6MP(3072X2048)30/25; 5MP(3072X1728)30/25; 2560*2048p:30/25; 2560*1920P30/25; 3MP(2048X1536)30/25; 2MP(1920X1080)30/25
--------------	---

Mechanical

Preset Position	255
Environmental	IP67 rating for outdoor use. Corrosion Resistant treated housing for salt spray environment. Built-in Face-plate Heater, Nitrogen Pressurized Housing, Sun-shield included, -40°C to +60°C operating temperature., Water Proof Connector.
Infrared	The adaptive infrared Illumination distance is up to 60 Meters.

Interface

Network	10M/100M/1000M Base-TX Ethernet, RJ45
Edge Storage	Micro SD, Up to 128GB(Optional)

Network

Video Compression	MJPEG,H.264, H.265
Protocols	L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTP,RTSP,QoS,DNS,DDNS,NTP, P,SNMP,SIP
Multi-stream	Triple stream
Compatible Integration	ONVIF 2.4

General

Operating Temperature	-40■ to +60■
Operating Humidity	80% Suitable for Use
Power Input	PoE+ (IEEE 802.03at)
Power Consumption	10W■Close IR■ 15W■Open IR■
Dimension	Φ120×278mm
Weight	2.3kg
Gross Weight (Approximate)	3KG/6.6LBS
Packing Dimension (Approximate)	cm: W43XD29XH29; Inch: W17XD11XH11