

Key Digital KD-X411ProK HDMI via CAT5e/6 Extender (Transmitter/Receiver) Kit with Audio De-Embedding

Technical:

- Inputs Tx (Each): 1 HDMI, 1 IR In, 1 Bi-Directional RS-232
- Outputs Tx (Each): 1 CAT5e/6 UTP/STP, 1 IR Out, 1 Analog Audio, 1 Digital Audio
- Inputs Rx (Each): 1 CAT5e/6 UTP/STP, 1 IR In
- Outputs Rx (Each): 1 HDMI, 1 Bi-Directional RS-232
- DDC Signal (Data): Input DDC Signal: 5 Volts p-p (TTL)
- HDMI Video/Audio Signal: Input Video Signal: 1.2 Volts p-p
- HDMI Connector: Type A, 19 Pin Female
- RJ45 Connector: Shielded Link Connector, HDBaseT
- IR Connectors: 3.5 mm stereo mini jack
- RS-232 Connector: 3.5 mm stereo mini jack

General:

- Regulation: CE, RoHS, WEEE
- Enclosure: Black Metal
- Product (Each): 5" x 4.06" x 1.06", Weight: 0.5 lbs
- KD-X411ProK Power: (2) KD-PS5V2ASC, 5V/2A, 100-240VAC, 50-60Hz, Interchangeable head with screw-in connector
- KD-X411POHK Power (Tx Only): KD-PS12V2ASC, 12V/2A, 100-240VAC, 50-60Hz, Interchangeable head with screw-in connector
- Accessories: (2) Mounting Brackets, (1) IR Emitter, (1) IR Sensor