

Key Digital KD-X200ProK HDBaseT/HDMI via Single CAT5e/6 Extender (Transmitter/Receiver) Kit with 4K

Technical:

- Inputs Tx (Each): 1 HDMI, 1 IR In
- Outputs Tx (Each): 1 CAT5e/6 UTP/STP, 1 IR Out /RS-232 Bi-Directional
- Inputs Rx (Each): 1 CAT5e/6 UTP/STP, 1 IR In
- Outputs Rx (Each): 1 HDMI, 1 IR Out /RS-232 Bi-Directional
- DDC Signal (Data): Input DDC Signal: 5 Volts p-p (TTL)
- HDMI Video/Audio Signal: Input Video Signal: 1.2 Volts p-p
- HDMI Connector: Type A, 19 Pin Female
- RJ45 Connector: Shielded Link Connector, HDBaseT
- IR In Connector: 3.5 mm stereo mini jack
- IR Out (RS-232) Connector: 3.5 mm stereo mini jack

General:

- Regulation: CE, RoHS, WEEE
- Enclosure: Black Metal
- Product (Each): 4.125" x 2.625" x 0.875", Weight: 0.5 lbs
- KD-X200ProK Power: (2) KD-PS5V2ASC, 5V/2A, 100-240VAC, 50-60Hz, Interchangeable head with screw-in connector
- KD-X200POHK Power (Tx Only): KD-PS12V2ASC, 12V/2A, 100-240VAC, 50-60Hz, Interchangeable head with screw-in connector
- Accessories: (2) Mounting Brackets, (1) IR Emitter, (1) IR Sensor