

Gefen GTV-HDMI-2-COMPSVIDS Gefen HDMI to Composite Video and S-Video Down-Converter

Gefen HDMI to Composite Video and S-Video Down-Converter. Model: GTV-HDMI-2-COMPSVIDS

Watch HDMI Video on your Composite or S-Video System -- with Audio

The new GefenTV HDMI to Composite Scaler lets you transform HDMI video of any resolution from 480i to 1080i into Composite video or S-Video, properly sized to view optimally on your display.

How it works

Simply connect your HDMI video source to the HDMI input jack of the GefenTV HDMI to Composite Scaler. Connect your Composite or S-Video display cable to the correct video output jack on the Scaler's rear panel. RCA-type analog audio output jacks and Coaxial S/PDIF digital audio output jacks allow for the connection of an audio receiver or other device to receive the audio signal embedded in the HDMI signal. Power-cycle all connected components, then use the IR remote control to activate the onscreen menu and adjust the settings to your liking. You will then have HDMI video playing on your Composite or S-Video display with simultaneous audio out.

Note: This device does NOT convert HDCP HDMI signals.

This device supports both NTSC and PAL video standards.

Features:

- HDMI to Composite / S-Video conversion plus scaling
- HDMI pass-through
- Supports 480i to 1080i HDMI input resolutions
- Outputs 480i / 576i signal for Composite/S-Video
- Supports both NTSC and PAL formats

Specifications:

- Input Video Signal: 1.2V p-p
- Input Sync Signal: 5V p-p (TTL)
- Horizontal Frequency Range: 15-70 KHz
- Vertical Frequency Range: 30-170 KHz
- Video In/Out: 1 L/R Composite RCA / 1 S-Video
- Audio In/Out: 2 L/R RCA audio, 2 S/PDIF digital audio
- Power Consumption: 13 Watts (maximum)
- Power Supply: 5V DC