

# Adder AVX5016IP AdderView KVM CATxIP 5000 Switch/16 Port

## Video modes

Support for standard PC, Sun and Mac video modes up to a resolution of 1600 x 1200 @ 60Hz. DDC emulation supported via connected Computer Access Modules (CAMs).

## Hardware compatibility

Video, mouse and keyboard for PC, Sun, Mac, RS/6000, Alpha and SGI computers using PS/2, USB or Sun flash upgradable Computer Access Modules (CAMs).

## OS compatibility

Operates with all currently known software and operating systems including all Windows versions, DOS, Linux, Unix, BSD, all Sun OS, all Mac OS and NetWare.

## Local console

Video: HDD15 socket  
Keyboard/Mouse: USB type A sockets

## Connections

Local console connections as stated above.  
CATx computer connections: all RJ45 style.  
10/100 auto-sensing Ethernet network port: RJ45.  
Power connection: 2.5mm DC jack (5V DC, 2.5A).  
RS232 triggered power switching and syncing: DB9 plug

## Physical design

Compact 1U high metal case construction suited for rack mounting (rack mount kits available).  
Width: 198mm/7.92", Height: 44mm/1.76", Depth: 120mm/4.8".  
Weight: 0.77kg/1.70lbs.

## Power supply

Mains adaptor with IEC style power lead (included).  
Input: 100-240VAC 0.5A 50-60Hz  
Output: 5VDC 2.5A

## Operating temperature

0°C to 40°C / 32°F to 104°F