

PureLink VIP-100H II Tx HDMI over IP Extension Extender (Transmitter)/Full HD

HARDWARE	
AUDIO	HDMI w/embedded audio
CABLING	Cat 5 UTP or better
INPUT SIGNAL TYPES	(Tx) HDMI v1.3, RS232 (Rx) RJ-45, H.264 UDP Multicast, RS232, IR
OUTPUT SIGNAL TYPES	(Tx) RJ-45, H.264 UDP Multicast, RS232 (Rx) HDMI v1.3, RS232, IR
PERFORMANCE	
SUPPORTED DISTANCE	120 m / 390 ft.
DATA TRANSFER RATE	15Mbps (typical)
SUPPORTED RESOLUTIONS	Up to1080p / 1920x1080
HDCP COMPLIANCE	1.3
RS-232	2400-115K baud, user-settable
IR EXTENSION	Rx to Tx (38-56 KHz)
CONNECTOR(S)	
CONNECTOR TYPES (TX)	2 - HDMI (19 pin) Female 1 - RJ-45 Female (LAN) 1 - Phoenix 3pin (RS232) 1 - 1/8" Female (IR)
CONNECTOR TYPES (RX)	1 - HDMI (19 pin) Female 1 - RJ-45 Female (LAN) 1 - Phoenix 3 pin (RS232) 1 - 1/8" Female (IR)
POWER	
INPUT POWER REQUIREMENTS	5 VDC, 600mA typical
POWER ADAPTER	120-240 VAC to 5 VDC, 1A
PoE (POWER OVER ETHERNET)	802.3af
DIMENSIONS & WEIGHT	
ENCLOSURE TYPE	All metal, black powder coat finish
DIMENSIONS	1.1" x 4.7" x 3.1 (29 mm x 120 mm x 79 mm)
WEIGHT	0.61 lbs [280 g]