

Adder X200A/R PS/2 KVM Extender Receiver/Audio/No De-skew up to 330ft

Video Resolution

1920 x 1200 at distances up to 50 m/165 ft.

1600 x 1200 at distances up to 200 m/650 ft.

1280 x 1024 at distances up to 300 m/1000 ft.

Extension Distance

Up to 300 m/1000 ft. using CATx cable (x=5,5e,6)

Devices Supported

Supports computers with USB style keyboard and mice, flat-screen and CRT style monitors with standard HDD-15 video connectors and optional audio through 3.5 mm audio jack.

O/S Compatability

All known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, Sun OS, Solaris, Mac OS, NetWare etc.

Connectors (USB CAM)

Video: HDD-15 Optional audio: 3.5 mm jack

Keyboard, Mouse: USB type A CATx: RJ45 connector

Connectors (X200 remote unit)

Video: HDD-15 Optional audio: 3.5 mm jack

Keyboard, Mouse: USB Type A CATx: 2 x RJ45 connector

Power: 2.5 mm DC jack

Physical (USB CAM) Combination of plastic enclosure and cables.

Enclosure: 64 mm/2.5 in. x 45 mm/1.8 in. x 25 mm/1 in.

Cables: 340 mm/13.4 in. long

Physical (X200 remote unit)

All metal case, 172 mm/6.8 in. x 26 mm/1 in. x 75 mm/3 in. 2.5 lb.

Power Supply

100 - 240VAC 50/60Hz (X200 remote unit only)

Available in following versions:

Order Codes

XX= Mains Lead Country Code:

UK= United Kingdom

US = United States

EURO = Europe

AUS = Australia

Additional Computer Access Modules (for second computer):

CATX-USB (USB computer access module)

CATX-USBA (USB computer access module with audio)

CATX-PS2 (PS2 computer access module)

CATX-PS2A (PS2 computer access module with audio)

CATX-SUNA (Computer access module with audio for Sun)

Approvals

CE, FCC