

Adder X2-SILVER/P CAT6 KVM Extender with RS232/DeSkew up to 1000 feet

Mechanical	Local Unit	Remote Unit
Height	1 in. (26 mm.)	1 in. (26 mm.)
Width	6.7 in. (172 mm.)	6.7 in. (172 mm.)
Depth	2.9 in. (75 mm.)	2.9 in. (75 mm.)
Rack Space	16 units fit into 2U of rack space	16 units fit into 2U of rack space
Environmental		
Temperature Tolerance	0-40°C (32 to 104°F)	
Humidity Tolerance	5 to 60% non condensing	
Power		
Operating Voltage	100-240VAC	
Power Frequency	50-60Hz	
Usage	5VDC at 500mA	
Connectors (Local computer-end unit)		
Computer	1 x 25-way female	
CATx cable	1 x RJ45	
Optional power adapter	2.5mm DC jack (only required for video only applications)	
Connectors (Remote console-end unit)		
Keyboard	1 x purple 6-pin mini-DIN female	
Mouse	1 x green 6-pin mini-DIN female	
Monitor	1 x blue 15-pin high-density D-type female	
CATx cable	1 x RJ45	
Power adapter	2.5mm DC jack	
Video Resolutions		
1600 x 1280		