

**Adder X2-DA-SILVER Dual Access CAT6 KVM Extender with RS232 up to 1000ft**

Mechanical	Local Unit	Remote Unit
Height	1 in. (26 mm.)	3.1 in. (80 mm.)
Width	6.7 in. (172 mm.)	6.7 in. (172 mm.)
Depth	2.9 in. (75 mm.)	2.9 in. (75 mm.)
Rack Space	16 units fit into 2U of rack space	5 units fit into 2U of rack space
Environmental		
Temperature Tolerance	0-40°C (32 to 104°F)	
Humidity Tolerance	5 to 60% non condensing	
Power		
Operating Voltage	100-240VAC	
Power Frequency	50-60Hz	
Usage	5VDC at 500mA	
Connectors		
Computers	1 x 25-way female	N/A
CATx cable	1 x RJ45	1 x RJ45
Serial	1 x DB9	1 x DB9
Keyboard	1 x purple 6-pin mini-DIN female	1 x purple 6-pin mini-DIN female
Mouse	1 x green 6-pin mini-DIN female	1 x green 6-pin mini-DIN female
Monitor	1 x blue 15-pin high-density D-type female	1 x blue 15-pin high-density D-type female
Power adapter	2.5mm DC jack optional power adapter (only)	