

## Kramer VS-1202xl 12x2 Composite Video and Balanced Stereo Audio Matrix Switcher

INPUT:	16/12/10 composite video, 1Vpp/75ohm on BNC connectors. 16/12/10 balanced (or unbalanced) audio stereo, + 4dBu/47kohm on detachable terminal blocks.
OUTPUT:	2 composite video, 1Vpp/75ohm on BNC connectors. 2 balanced (or unbalanced) audio stereo, + 4dBu/50ohm (20 Vpp max.) on detachable terminal blocks.
VIDEO BANDWIDTH (-3dB):	200MHz.
AUDIO BANDWIDTH (-3dB):	100kHz.
DIFF. GAIN:	0.04%.
DIFF. PHASE:	0.04 Deg.
K-FACTOR:	0.05%.
VIDEO S/N:	73dB.
AUDIO S/N:	82dB unweighted, (1Vpp).
VIDEO CROSSTALK:	<60dB @ 5MHz.
NON-LINEARITY:	0.05%.
CONTROL:	Manual, RS-232 or RS- 485.
AUDIO THD:	0.021% (1V, 1kHz).
2nd Harmonic	0.004%.
SWITCHING:	Vertical interval.
POWER SOURCE:	230V AC, 50/60 Hz, (115V AC, USA) 10VA.
DIMENSIONS:	19-inch (W), 7-inch (D) 2U (H) rack mountable.
WEIGHT:	3.4 Kg (7.5 Lbs.) approx.
ACCESSORIES:	Power cord, Windows® - based control software, Null modem adapter.