

Avenview HDM-C6MWIP-S H264 HDMI over IP Extender (Transmitter) with Switching/Videowall

ITEM	DESCRIPTION
UNITS	HDM-C6MWIP-S
UNIT DESCRIPTION	HDMI Transmitter/Encoder
INPUT VIDEO PORT	HDMI
SUPPORTED RESOLUTIONS	HDMI 640 x480@60Hz up to 1920 x1200@60Hz DVI up to 1920 x1200@60Hz VGA up to 1920 x1200@60Hz YPbPr up to 1920 x1080i@60Hz CVBS up to 576i@50Hz <i>(For more details check User Guide)</i>
OUTPUT VIDEO PORTS	LAN
OUTPUT VIDEO TYPE	H.264/MPEG-4 AVC
OUTPUT VIDEO RESOLUTION	Large IP stream: 480p@60Hz~1920 x 1200@60Hz Small IP stream: 352x288@5Hz
VIDEO IMPEDENCE	100 Ω
END-TO-END LATENCY	About 60ms-90ms (Low latency mode) About 250ms-300ms (High quality mode)
INPUT AUDIO PORTS	Audio jack
INPUT AUDIO FORMAT	Stereo
OUTPUT AUDIO PORTS	Phoenix connector
OUTPUT AUDIO FORMAT	Stereo
CONTROL METHOD	Rear panel source switch, PC configurator and RS-232
DIMENSIONS (L X W X H)	7.9" x 1.0" x 3.7"
WEIGHT	1 lbs
POWER SUPPLY	12 V 1A DC
ENVIRONMENTAL	
OPERATING TEMPERATURE	32? ~ 104?F (0? to 40?C)
STORAGE TEMPERATURE	-4? ~ 140?F (-20? ~ 60?C)
RELATIVE HUMIDITY	20~90% RH (non-condensing)