

Avenview HDM-C6MWIP-SET HDMI H.264 IP Matrix Decoder/Encoder Over CATx w VW Mode

Units	HDM-C6MWIP-S	HDM-C6MWIP-R
Input Video Port	DVI IN	LAN
Input Video Type	HDMI, DVI 1.0, VGA, YPbPr, CVBS	H.264/MPEG-4 AVC
Input Resolution	HDMI 640 x480@60Hz up to 1920x1200@60Hz DVI up to 1920 x 1200@60Hz VGA up to 1920 x 1200@60Hz YPbPr up to 1920 x 1080i@60Hz CVBS up to 576i@50Hz	480p@60Hz~ 1920x 1200@60Hz
Video Impedance	100Ω	100 Ω
Output Video Port	LAN	HDMI
Output Video Type	H264/MPEG-4 AVC	HDMI 1.3
Output Resolution	Up to 1920 x 1200@60Hz	HDMI up to 1920x 1200@60Hz
Input Audio Port	Audio jack	LAN
Output Audio Port	Phoenix connector	Phoenix connector
Power Supply	12V 1 A DC	12 V 1 A DC
Dimensions (LXWXH)	7.9" x 3.7 x 1.0"	2.2"x7.1Hx3.0M
Weight	1 lbs	1.3 lbs