

Kramer 905xl Stereo Audio Power Amplifier (110 Watts per Channel)

INPUTS

- 1 unbalanced stereo audio on RCA connectors
- 1 balanced stereo audio on a 5-pin terminal block connector

OUTPUT

- 1 speaker stereo audio on a 4-pin terminal block connector

INPUT SENSITIVITY

- 760mVpp (unbalanced)
- 1.2Vpp (balanced)

OUTPUT POWER

- 55W per channel into 8 Ω
- 110W per channel into 4 Ω

MAX. VOLTAGE GAIN

- 8 Ω : 49dB (unbalanced)
- 45dB (balanced) 4 Ω : 47dB (unbalanced)
- 44dB (balanced)

OUTPUT MUSIC POWER

- 300W per channel into 4 Ω

BANDWIDTH (-3DB)

- >26kHz

S/N RATIO

- 80dB

CROSSTALK

- -120dB @1kHz
- -111dB @20kHz

CONTROLS

- Bass: -15dB to 14dB @100Hz
- mid: -13.7dB to 13.7dB @1kHz
- treble: -13.7dB to 13.8dB @10kHz
- balance: -46.9dB to 0dB
- volume: -80dB to 32dB @1kHz

ADDITIONAL CONTROLS

- Loudness: -9dB @500Hz
- -9dB @1kHz
- -8.5dB @15kHz

COUPLING

- Input: AC
- Output: DC

AUDIO THD + NOISE

- <1% @1kHz
- 1V

AUDIO 2ND HARMONIC

- <0.1% @1kHz

AMPLIFIER TYPE

- Class D

POWER CONSUMPTION

- 220/110V AC
- 50/60Hz
- 510VA

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%
- RHL non-condensing

INCLUDED ACCESSORIES

- Power cord
- rack "ears"

PRODUCT DIMENSION

- 19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

PRODUCT WEIGHT

- 1.4kg (3.1lbs) approx

SHIPPING DIMENSION

- 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

SHIPPING WEIGHT

- 2.2kg (4.9lbs) approx