



## 914

Stereo Power Amplifier (100 Watts per Channel)

| Speakers



The Kramer 914 is a highperformance 2x100W power amplifier that accepts a balanced stereo audio input on a 5pin terminal block and converts the signal into a differential stereo audio output for speakers on a 4pin terminal block

### FEATURES

- Stereo Mode - 2x100W @4
- BTL Mode - 1x200W @8
- ENERGY STAR® Compliant
- Class D Amplifier
- Input Level Sensitivity Adjustment
- Remote Control - Volume, standby and mute
- Audio Level Knob
- Operating Modes - Stereo and bridged mono
- Indicators - Independent left and right channel monitoring LEDs
- Connectors - Easytoconnect, detachable terminal blocks



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUT:	1 balanced stereo +4dBu/10k on a 5pin removable terminal block
OUTPUT:	1 stereo or bridged mono speaker output on a 4pin removable large terminal block
INPUT SENSITIVITY:	0.3V to 1.23V -10dBu to 4 dBu
OUTPUT POWER:	2x100W @4, 2x50W @8, 1x200W @8 BTL
AMPLIFIER TYPE:	Class D
MAXIMUM VOLTAGE GAIN:	22.7dB
BANDWIDTH (-3dB):	20Hz to 20kHz
S/N RATIO:	-70dB @ 14dBu amplification
CONTROLS:	Screw trimmer for line input sensitivity, remote 10k trimmer, contactclosure controls for mute and standby
AUDIO THD+NOISE:	0.05% @75W RMS @4 6.67kHz
PRODUCT DIMENSION:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72" ) W, D, H
PRODUCT WEIGHT:	1.3kg (2.8lbs) approx
SHIPPING DIMENSION:	40.50cm x 29.70cm x 9.00cm (15.94" x 11.69" x 3.54" ) W, D, H
SHIPPING WEIGHT:	1.7kg (3.8lbs) approx
AUDIO 2nd HARMONIC:	0.08% @75W RMS @4 6.67kHz
POWER SOURCE:	See label near rear panel power socket: USA version: 100120V AC, 50/60Hz, 360VA; European version: 200240V AC, 50/60Hz, 420VA
INCLUDED ACCESSORIES:	Power cord, mounting bracket
OPTIONS:	RK1 19" rack adapter

