

# Kramer 920 Power Amplifier (200W into 70V/100V)

## INPUT

- 1 balanced stereo +4dBu/10kΩ on a 5-pin removable terminal block
- 1 unbalanced stereo on 2 RCA connectors

## OUTPUT

- 1 speaker 70/100V output on a 3-pin removable
- large terminal block

## INPUT SENSITIVITY

- 0.3V to 1.23V
- -10dBu to 4dBu

## OUTPUT POWER

- 200W

## AMPLIFIER TYPE

- Class D

## MAXIMUM VOLTAGE GAIN

- +26dB

## BANDWIDTH (-3DB)

- 20Hz to 20kHz

## S/N RATIO

- -75dB @14dBu amplification (0.039%)

## CONTROLS

- Screw trimmer for line and mic input sensitivity

## HIGH PASS FILTER

- When on, frequencies below 120Hz are attenuated by 12dB per octave:
- -12dB @120Hz
- -24dB @60Hz
- -36dB @30Hz

## INPUT SATURATION

- Maximum input level is 3.9Vpp @-48dB

## AUDIO THD + NOISE

- 70v main output: -71dB @7.8dBu amplification
- 100v main output: -72 db @8.3dBu amplification

## AUDIO 2ND HARMONIC

- 0.08% for 70v/100v output

## POWER SOURCE

- See label near rear panel power socket:
- USA version: 100-120V AC, 50/60Hz, 330VA; European version: 200-240V AC, 50/60Hz, 480VA

## INCLUDED ACCESSORIES

- Power cord
- rack "ears"

## PRODUCT DIMENSION

- 19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

## PRODUCT WEIGHT

- 4.7kg (10.4lbs) approx

#### SHIPPING DIMENSION

- 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21" ) W, D, H

#### SHIPPING WEIGHT

- 5.6kg (12.3lbs) approx