

Apantac MD-12-4# Cost Effective Dual Output Hybrid (16x2) (12 SDI+4 HDMI) Multiviewer

MODEL	MD-X-X# Cost Effective Dual Output Hybrid (16x2) (HDMI+SDI) Multiviewer		
Inputs	Combinations of HDMI and 3G/HD/SD-SDI	Video Outputs	2 independent DVI/HDMI, SDI outputs
HDMI Connectors	HDMI Type-A Female	Audio Outputs	AES and Analog audio monitor outputs
SDI Connectors	BNC IEC 61169-8 Annex A	Output Resolution	1920 x 1080p 50/60Hz
Total Windows	32+	On-Screen Display	Borders, labels, tally UMD, OMD, IMD, dynamic UMD
HDMI	480P, 720P, 1080i, 1080P 50/60Hz	General Purpose IO	Up to 32 inputs with RJ50 - DB9 connectors
Serial Digital	SMPTE 424M, 292M, 259M	Serial Port	Connector: RJ45, Baud Rate up to 115200 Format, TSL, TSI, AXP
HDMI Audio	4 channels per input	IP	100 Base-Tx, TSL, AXP Connector: RJ45
SDI Audio	SMPTE-272M-A	Electrical	50W, 90-250V 50/60 Hz
Alarms	No audio, audio high/low, no video	EMI/RFI	Complies with FCC Part 15 Class A, CE, EU EMC, C-tick
Power	90-250 AC / 12 DC	Size	1 RU, 25 cm (10")