

| | | |
|---------------------------|--|---|
| Panel | Panel Type: | LED-Backlit TFT LCD (IPS Technology) |
| | Panel Size: | 64.5 |
| | Max. Resolution: | UHD 3840 x 2160 |
| | Pixel Pitch: | 0.372 mm |
| | Brightness: | 350 cd/m ² |
| | Contrast Ratio: | 1200:1 |
| | Viewing Angle (H/V): | 178°/178° |
| | Display Colour: | 1.07B |
| | Response Time: | 5 ms |
| Surface Treatment: | Anti-Glare Treatment (Haze 25%), 3H Hard Coating | |
| Touch Screen | Panel Interface: | USB 2.0 x 2 (Type-B) |
| Frequency | Frequency (H): | 30 kHz-80 kHz |
| | Frequency (V): | 50 Hz-76 Hz |
| Signal Input | HDMI: | 2.0 x 3 |
| | VGA: | 15-Pin D-Sub x 1 |
| Signal Output | HDMI: | 2.0 x 1 |
| External Control | RS232 In: | 9-Pin D-Sub |
| | LAN: | RJ45 x 1 |
| Embedded Player | OS: | Android 8.0 |
| | CPU: | Dual core A73+Dual core A53 |
| | Memory: | 3 GB |
| | Storage: | 16 GB |
| Other Connectivity | USB: | 2.0 x 3 / 3.0 x 3 |
| Audio | Audio In: | Stereo Audio Jack (3.5 mm) |
| | Audio Out: | Stereo Audio Jack (3.5 mm), S/PDIF |
| | Internal Speakers: | 16W x 2 |
| Touch Screen | Technology: | Infrared Touch Frame |
| | Positional Accuracy: | ±1.5mm |
| | Single Touch Plug & Play: | Windows 2000/XP/Vista/CE 6.0macOS |
| | Multi-touch Plug & Play: | Windows 7/8/10Android/Linux (kernel version 3.5+)Chrome OS (39 or above) |
| | Multi-touch Support by Driver: | macOS (supported by UPDD driver) |
| Power | Power Supply: | Internal |
| | Power Requirements: | AC 100-240V, 50/60 Hz |
| | On Mode: | 155W |
| | Stand-by Mode: | < 0.5W |

| | | |
|-----------------------------|---------------------------------|--|
| | Off Mode: | < 0.5W |
| | Thickness: | 4.0 mm (0.16") |
| | Reflection Rate: | < 10% |
| | Transmission Rate: | ≥ 88% |
| | Hardness: | ≥ 8H |
| Operating Conditions | Temperature: | 0°C-40°C (32°F-104°F) |
| | Humidity: | 10%-90% (non-condensing) |
| Storage Conditions | Temperature: | -20°C-60°C (-4°F-140°F) |
| | Humidity: | 10%-90%(non-condensing) |
| Mounting | VESA FPMPI: | Yes (600 x 400 mm) |
| Dimensions | Product w/o Base (W x H x D): | 1489.0 x 897.0 x86.0 mm(58.6" x 35.3" x 3.4") |
| | Packaging (W x H x D): | 1656.0 x 1050.0 x 204.0 mm(65.2" x 41.3" x 8.0") |
| Weight | Product w/o Base: | 39.0 kg (86.0lb) |
| | Packaging: | 55.7 kg (122.8 lb) |
| Regulation Approval | Certifications & Compliance: | CE, LVD, FCC, WEEE, REACH, RoHS, BSMI |
| Accessories | Supplied: | Power Cord, HDMI Cable, USB Cable, Remote Control, Batteries, Quick Start Guide, Touch Pen, Wall Mount, Wi-Fi / Bluetooth Module |
| Optional Accessories | Floor Mount (Landscape only): | FMC-03+LMK-04, FMC-04+LMK-04 |
| | Ceiling Mount (Landscape only): | CMP-01+LMK-01 |
| | Wall Mount (Landscape only): | LMK-01, LMK-03 |
| | Stand: | STD-08 |