

Soundtube IPD-SM82-EZ-II-BK Dante enabled 8 inch Two-way Surface mount speaker (Black)

| | |
|---|--|
| System Type | Controlled |
| Frequency Response (- 3 dB) | 50 Hz - 20 kHz Sealed: 70 Hz - 20 kHz |
| Frequency Response (- 10 aB) ¹ | 38 Hz - 20 kHz Sealed: 50 Hz - 20 kHz |
| Max. Power SPL _{1m} | 101.0 dB |
| Coverage Angle (-6 dB @ 2 kHz) | 70° Horizontal / 90° Vertical |
| Coverage Angle (-6 dB @ 10 kHz) | 110° Horizontal / 100° vertical |
| Coverage Angle (averaged 2-10 kHz) | 90° horizontal / 105° vertical |
| Aiming Angle | 0°-0Cr |
| Directivity Factor (Q) | 5.20 (Averaged 100 Hz -10 kHz): 12.0 @ 2 kHz |
| Directivity Index (DI) | 6.20 (Averaged 100 Hz -10 kHz): 10.8 @ 2 kHz |
| Transducer - Low-Frequency Driver | 203.0 mm (8.0 in.) polypropylene woofer with butyl rubber |
| Transducer - High-Frequency Driver | 25.0 mm (1.0 in) soft dome tweeter |
| Low-Frequency Voice Coil | 38.1 mm (1.50 in) high temperature Kapton |
| Crossover Frequency | 2.5 kHz |
| Network Type - Low Pass | 12 dB per octave. 2nd order |
| Network Type-High Pass | 12 dB per octave. 2nd order |
| Enclosure Material | High Impact Poly Styrene (HIPS) |
| Grille | Aluminum with powder-coat finish |
| Inputs | FU45 Ethernet Port |
| Colors | Black or white |
| Height | 457.2 mm (18.00 in.) |
| Width | 292.1 mm (11.50 in.) |
| Depth | 251.0 mm (9.88 in.) |
| Weight | 6.3 kg (13.9 lbs.) |
| Weight in Shipping Configuration | 7.0 kg (15.4 lbs.) |
| Included Accessories | Safety cable, wall mount bracket, port plug, allen wrench and watertight strain-relief bushing |
| Packaging | One per box |
| Regulatory - CE | Approved |
| Regulatory - UL | UL 60065 Listed |
| RoHS Compliant | Approved |
| IP65 (sealed version) | Approved |