

## Smartavi MXU-88S 8x8 HDMI/USB 2.0 Matrix Switch w 4K Res and Keyboard-Mouse Capabilities/No Emulation

VIDEO & AUDIO	
Input Interface	(8) HDMI Type-A 19-pin Female TMDS
Output Interface	(8) HDMI Type-A 19-pin Female TMDS
Max. Resolution	Up to 4K (3840×2160 @ 30Hz)
HDMI Version	HDMI 1.4
Video Bandwidth	300 MHz
Max. Cable Length	Up to 20 ft.
Audio	Stereo Embedded in HDMI signal
USB	
Signal Type	USB 2.0, 1.1, and 1.0
Input	(8) USB Type B Female (No Emulation)
Output	(16) USB Type A Female
CONTROL	
Front Panel	Front panel buttons
Ethernet (TCP/IP)	via RJ-45
OTHER	
Power Supply	Internal 100-240 VAC/12 DC, 2A
Max. Consumption	100 W
Dimensions	17.06" W x 2.0" H x 10.4" D
Weight	8.8 lbs
Operating Temp.	32 to 122°F (0 to 50 °C )
Storage Temp.	-4 to 149 °F (-20 to 65 °C )
Humidity	Up to 85% RH (non-condensing)