

**Aurora Multimedia IPX-TC3-WP-C-B 4K HDMI 10Gbps AV-over-IP Transceiver Wall Plate Copper Version (Black)**

<b>Video</b>	
Compression	Zero (4K30 4:4:4/4K60 4:2:0), 1.3:1 (4K60 4:4:4)
Latency	Zero Frame Latency (100us without Scaling, 3ms with Scaling)
Bandwidth	600MHz
<b>Connectors</b>	
HDMI	2 Inputs, 1 Output
Audio Analog	Stereo Line-In/Out (3.5mm)
Ethernet	10G Fiber SFP+, 10G Copper RJ-45 330ft CAT 6A PoE+
RS-232	Up to 115k Baud (3.5mm TRS Tip TX, Ring RX, Sleeve Ground)
IR	Bi-Directional (3.5mm TRS Tip TX, Ring 5V, Sleeve Ground)
USB	2 x USB 2.0 Type A, 1 x USB 2.0 Micro
Expansions	ExtremeUSB, Dante and ReAX Options
<b>Control</b>	
Webserver	Built-In Control Server
Windows / Linux	IPBaseT Manager Software Compatible
Interface	IR or Keypad
<b>Physical &amp; Power</b>	
Housing	Black Aluminum Enclosure
Dimensions [L x W x H]	3 Gang 5.54" x 2.83" (4.331" with mounting tabs) x 1.404" (1.5" with option card)
Weight	0.943 kg [2.08 lbs]
Mounting	Wall-mounting Decora 3 Gang (Optional: Rack mount vertical, horizontal, under table.)
Power Supply	48V DC (2 pin Euro) or PoE+ 25.4W (LAN)
Power Consumption	18 Watts
Operation Temperature	0 ~ 40 Celsius [32 ~ 100 Farenheit]
Storage Temperature	-20 ~ 60 Celsius [-4 ~ 140 Farenheit]