

## Electro-Voice EVIDC6.2 6.5 inch EVID Series Ceiling Speaker/White (PAIR)

Frequency response:	50 Hz - 20 kHz
Sensitivity (SPL 1 W/1 m):	90 dB
Coverage pattern:	120° conical
Power handling (@ 8Ω):	75 W (with overload protection)
Rated Impedance:	8 Ω
Recommended High-Pass frequency:	60 Hz
Input configuration:	8Ω; 70V/100V
70V/100V power taps:	1.8 (70V only)/3.7/7.5/15/30 W
LF transducer:	6.5 in (165 mm) high-compliance driver (weatherized cone)
HF transducer:	1 in (25 mm) Ti-coated dome
Mounting system:	Integrated 4-point toggle anchors
Acoustic design:	Ported cabinet, two-way design, internally damped, w/passive crossover
Cabinet construction:	Steel enclosure and UL94V-0 rated baffle and bezel
Grille construction:	Powder-coated steel
Color:	White (paintable)
Cutout dimensions (diam.):	10.6 in. (269 mm)
Dimensions (depth x diam.):	7.0 in. x 11.8 in. (190 mm x 300 mm)
Net weight:	10 lb (4.5 kg)
Included accessories:	Tile bridge, mounting ring
Safety agency ratings:	UL 1480 Safe for use in air handling spaces per UL 2043