

Aurora Multimedia IPX-TC3-CF-Pro 4K 10Gbps AV-over-IP Transceiver Box with 2 HDMI in/1 HDMI out (Copper and Fiber version)

Video	
Compression	Zero (4K30 4:4:4/4K60 4:2:0), 1.3:1 (4K60 4:4:4)
Latency	Zero Frame Latency (100us without Scaling, 3ms with Scaling)
Bandwidth	600MHz
Connectors	
HDMI	2 Inputs, 1 Output
Analog Audio	Stereo Line-In/Out (3.5mm)
Ethernet	10G Fiber SFP+, 10G Copper RJ-45 330ft CAT 6A PoE+
RS-232	Up to 115k Baud (3.5mm TRS Tip TX, Ring RX, Sleeve Ground)
IR	Bi-Directional (3.5mm TRS Tip TX, Ring 5V, Sleeve Ground)
USB	2 x USB 2.0 Type A, 1 x USB 2.0 Micro
Expansions	ExtremeUSB, Dante and ReAX Options
Control	
Webserver	Built-In Control Server
Windows /Linux	IPBaseT Manager Software Compatible
Interface	IR or Keypad
Physical & Power	
Housing	Black Aluminum Enclosure
Dimensions [L x W x H]	190.2 x 150.51 x 31.12mm [7.49" x 5.91" x 1.23"]
Weight	0.943 kg [2.08 lbs]
Mounting	Wall-mounting Decora 3 Gang (Optional: Rack mount vertical, horizontal, under table.
Power Supply	48V DC (2 pin Euro) or PoE+ 25.4W (LAN)
Power Consumption	18 Watts
Operation Temperature	0 ~ 40 Celsius [32 ~ 100 Farenheit]
Storage Temperature	-20 ~ 60 Celsius [-4 ~ 140 Farenheit]