

Aten PE6324LG 32A 24-Outlet Metered and Switched Low Profile eco PDU

Function	PE6324LG
Electrical	
Nominal Input Voltage	100 – 240 VAC
Maximum Input Current	32A(Max)
Input Frequency	50-60 Hz
Input Connection	IEC 60309 32A
Input Power	7360 VA(Max)
Outlet Type	Total: 21 x IEC320 C13 + 3 x IEC320 C19 Bank1-1: Outlet 1 – 8; 7 x C13 + 1 x C19 Bank1-2: Outlet 9 – 16; 7 x C13 + 1 x C19 Bank2: Outlet 17 – 24; 7 x C13 + 1 x C19
Nominal Output Voltage	100 – 240 VAC
Maximum Output Current (Outlet)	C13: 10A(Max) C19: 16A(Max)
Maximum Output Current (Bank)	16A(Max)
Maximum Output Current (Total)	32A(Max)
Breakers	2 x 16A Slim Breaker
Metering	Bank Level Current, Voltage, VA , PF and kWh Monitoring
Outlet Switching	Yes
Environment Sensor Ports	2
Metering Accuracy	Voltage Range: 100VAC ~ 250VAC +/-1% Power Range: 100W ~ Maximum Capacity +/- 2% Current Range: 0.1A~1A +/- 0.1A, 1A~20A +/-1%
Physical Properties	
Dimensions (L x W x H)	177.50 x 6.60 x 4.40 cm (69.88 x 2.6 x 1.73 in.)
Weight	5.76 kg (12.69 lb)
Power Cord Length	1.6 m
Environmental	
Temperature (Operating / Storage)	0-40°C / -20-60°C
Humidity (Operating & Storage)	0-80% RH, Non-Condensing
Compliance	
EMC Verification	CE, C-Tick, Others by Request
Safety Verification	CE-LVD, Others by Request
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.