

Tannoy VSX 10BP 10 inch Compact Band Pass Passive Subwoofer for Portable and Installation Applications/Black

System Type	Subwoofer - Band pass
Frequency Response (-3 dB) (1)	42 Hz - 110 Hz
Frequency Response (-10 dB) (1)	36 Hz - 130 Hz
System Sensitivity (1 W @ 1 m) (2)	93 dB (1 W = 2.83 V for 8 ohms)
Power Handling	Average: 200 W Programme: 400 W Peak (10 ms): 800 W
Recommended Amplifier Power	400 W @ 8 Ohms
Rated Maximum SPL (2)	Average: 116 dB Peak: 122 dB
Nominal Impedance	8 Ohms
Driver Complement	250 mm (10") Bass driver
Recommended Crossover	80 Hz - 110 Hz, 24 dB / octave
Recommended Crossover	Recommended high-pass filter 40 Hz, 24 dB / octave
Distortion	
10% Full Power (28.3 V)	2nd Harmonic 50 Hz: 2.24%, 100 Hz: 0.17% 3rd Harmonic 50 Hz: 1.95%, 100 Hz: 0.47%
10% Full Power (28.3 V)	2nd Harmonic 50 Hz: 0.67%, 100 Hz: 0.42% 3rd Harmonic 50 Hz: 0.57%, 100 Hz: 0.49%
Construction	
Enclosure	61 litres, 15 mm birch plywood, internally braced
Connectors	2 x speakON NL4MP and Barrier strip
Fittings	8 x M10 flying inserts (landscape mounting, portrait only if ground stacked)
Fittings	1 x Integrip carrying handle
Dimensions (H x W x D)	300 x 460 x 590 mm (11.8 x 18.1 x 23.2")
Packed Quantity	1
Net Weight (ea)	18.5 kg (40.8 lbs)
Shipping Weight	22 kg (48.5 lbs)
Finish	
Colour	Black (Ral 9004)