

Aurora Multimedia DXW-2EU-S3-B 2 Input VGA/ HDMI/ LAN/ USB HDBaseT Wall Plate Extender (Transmitter/Receiver) Set with Audio I/O (Black)

DXW-2EU

| Video            |                                                                                                                                                 |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| HDMI Compliance  | HDMI 3D                                                                                                                                         |
| HDCP Compliant   | Yes                                                                                                                                             |
| Distance         | 330ft over one CAT 5e/6/7 cable (1080p 60Hz 48bit),500ft over one CAT 6 cable (1080p 60Hz 24bit),600ft over one CAT 6a cable (1080p 60Hz 24bit) |
| Max Resolution   | 4K x 2K                                                                                                                                         |
| Color Depth      | 48bit                                                                                                                                           |
| Connectors       |                                                                                                                                                 |
| Digital Video    | (1) HDMI in with 3.5mm TRS audio for DVI                                                                                                        |
| Analog Video     | (1) VGA in with 3.5mm TRS audio for DVI,Can be used for YPbPr/S-Video/Composite with optional break out cables                                  |
| Data             | (1) Ethernet port for network pass-through,(2) USB ports for pass-through and charging                                                          |
| Control          |                                                                                                                                                 |
| IR               | IR pass through for controlling remote devices                                                                                                  |
| Serial           | Capable of being controlled remotely through compatible receiver                                                                                |
| Physical & Power |                                                                                                                                                 |
| Dimensions       | 2 Gang 3.728” x 4.331” x 1.404” Note: Wall box portion depth 1.04”                                                                              |
| Weight           | 0.5lbs                                                                                                                                          |
| Power            | 24VDC & PoH                                                                                                                                     |

DXE-CAT-RX3

| Technical             |                                                              |
|-----------------------|--------------------------------------------------------------|
| Max Distance          | 600ft                                                        |
| Max Resolution        | 1080p 60Hz                                                   |
| Color Depth           | 48bit 330ft (CAT5e)24bit 600ft(CAT6A)                        |
| HDMI                  | 1.4 3D                                                       |
| Mechanical            |                                                              |
| Dimensions            | 215mm x 97mm x 33mm [8.46"L x 3.82"W x 1.3"H]                |
| Weight                | 2 lbs                                                        |
| Power supply          | 24V 24 Watt or 24V 90 Watt DC (Required on amplifier models) |
| Mounting              | Wall Mount                                                   |
| Operation temperature | 0~40°C [32~104°F]                                            |

PS0062-1

| Electrical        |                      |
|-------------------|----------------------|
| Input Voltage     | 100-240VAV 50/60Hz   |
| Output Voltage    | 24V DC               |
| Output Current    | 1A                   |
| Power             | 24 Watts             |
| Physical          |                      |
| Dimensions        | 76mm x 48mm x 28.7mm |
| DC Connector Plug | 5.5mm x 2.5mm x 11mm |
| Approvals         |                      |
| Agency            | FCC, CE, C-TICK, UL  |