

Soundtube IPD-SM52-EZ-WH Dante Enabled 5.25 Two-way Surface mount Speaker (White)

System Type	5.25-inch, coaxial, surface-mount. ported. Dante™ IP Controlled
Frequency Response (-3 dB)	65 Hz - 20 kHz Sealed: 80 Hz - 20 kHz
Frequency Response (-10 dB)	55 Hz - 20 kHz Sealed: 62 Hz - 20 kHz
Max. SPL dB @ 1 M RMS2	97.0 dB
Coverage Angle (-6 dB @ 2 kHz)	91° horizontal / 120° vertical
Coverage Angle (-6 dB @ 10 kHz)	70° horizontal / 110° vertical
Coverage Angle (Avq. 2 to 10 kHz)	95° horizontal / 100° vertical
Aiming Angle	0°-90°
Directivity Factor (Q)	6.9 (averaged 100hz-10khz); 5.9 (2kHz)
Directivity Index (DI)	5.2 (averaged 100hz-10khz); 7.7 (2kHz)
Low-Frequency Driver	1 x 133.0 mm (5.25 in) polypropylene cone, butyl rubber surround
High-Frequency Driver	25.0 mm (1.0 in) soft dome tweeter
Low-Frequency Voice Coil	25.4 mm (1.00 in) high temperature Kapton
Crossover Frequency	3.5 kHz
Network Type: Low-Pass	12 dB per octave. 2nd order
Network Type: High-Pass	12 dB per octave. 2nd order
Enclosure Material	High Impact Poly Styrene (HIPS)
Grille	Aluminum with powder-coat finish
Inputs	RJ45 Ethernet Port
Colors	Black or white (Custom colors available)
Height	301.8 mm (11.88 in)
Width	190.5 mm (7.50 in)
Depth (Without Bracket)	168.4 mm (6.63 in)
Weight	3.35 kg (7.4 lbs)
Shipping Weight	4.26 kg (9.4 lbs)
Included Accessories	Safety cable with speaker mounting bolt, wall mount bracket, port plug, allen wrench and water tight strain-relief bushing
Optional Accessories	N/A
Packaging	One per box
Regulatory - UL	UL60065 planned
Regulatory - CE	Approved
RcHS	Approved
IP65 (sealed version)	Approved