

Aurora Multimedia DXW-2EUH-S3-B 2 Input HDBaseT Wall Plate VGA/HDMI/ LAN/USB 2.0 Extender (Transmitter/Receiver) Set/Audio I/O (Black)

DXW-2EUH

Video	
HDMI Compliance	HDMI 3D
HDCP Compliant	Yes
Distance	330ft over one CAT 5e/6/7 cable (1080p 60Hz 48bit),500ft over one CAT 6 cable (1080p 60Hz 24bit),600ft over one CAT 6a cable (1080p 60Hz 24bit)
Max Resolution	4K x 2K
Color Depth	48bit
Connectors	
Digital Video	(1) HDMI in with 3.5mm TRS audio for DVI
Analog Video	(1) VGA in with 3.5mm TRS audio for DVI,Can be used for YPbPr/S-Video/Composite with optional break out cables
Data	(1) Ethernet port for network pass-through,(2) USB ports for pass-through (Top one only for Host)
Control	
IR	IR pass through for controlling remote devices
Serial	Capable of being controlled remotely through compatible receiver
Physical & Power	
Dimensions	2 Gang 3.728" x 4.331" x 1.404" Note: Wall box portion depth 1.04"
Weight	0.5lbs
Power	24VDC & PoH

DXE-CAT-RX3

Technical	
Max Distance	600ft
Max Resolution	1080p 60Hz
Color Depth	48bit 330ft (CAT5e)24bit 600ft(CAT6A)
HDMI	1.4 3D
Mechanical	
Dimensions	215mm x 97mm x 33mm [8.46"L x 3.82"W x 1.3"H]
Weight	2 lbs
Power supply	24V 24 Watt or 24V 90 Watt DC (Required on amplifier models)
Mounting	Wall Mount
Operation temperature	0~40°C [32~104°F]

PS0062-1

Electrical	
Input Voltage	100-240VAV 50/60Hz
Output Voltage	24V DC
Output Current	1A
Power	24 Watts
Physical	
Dimensions	76mm x 48mm x 28.7mm
DC Connector Plug	5.5mm x 2.5mm x 11mm
Approvals	
Agency	FCC, CE, C-TICK, UL

PS0080-1

Electrical	
Input Voltage	100-240V AC 50/60Hz
Output Voltage	24V DC

Output Current	.65A
Power	15.6 Watts
Physical	
Dimensions	74mm x 46.6mm x 28.7mm
DC Connector Plug	5.5mm x 1.35mm x 9mm
Approvals	
Agency	FCC, CE, C-TICK, UL