

Kramer FC-6 2-port Multi-Function Serial/IR Control Gateway

OUTPUTS

- 4 IR emitters when 2 multi-IO ports are IR-selected

PORTS

- 2 RS-232/IR multi-IO on 3-pin terminal blocks each selectable as either 1 bidirectional RS-232 or 2 IR emitters, 1 Ethernet on an RJ-45 connector, 1 mini USB connector for local services, 1 built-in IR sensor (for learning)

SUPPORTED SERIAL PORT BAUD RATES

- 1200, 2400, 4800, 9600, 19200, 38400, 57600, 15200bps

RS-232 COMMUNICATION

- Transparent up to 115200bps

IR EMITTER CABLE RANGE

- 80m (260ft)

SUPPORTED IR INPUT FREQUENCIES

- 20kHz to 60kHz

SUPPORTED IR OUTPUT FREQUENCIES

- 20kHz to 1.2MHz

MAXIMUM DATA HANDLING OF DEVICE

- Up to 150kbps summed on all ports

POWER CONSUMPTION

- 5V DC, 300mA

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

COOLING

- Convection

ENCLOSURE TYPE

- Aluminium

RACK MOUNT

- With optional rack adapter

ENVIRONMENTAL REGULATORY COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

INCLUDED ACCESSORIES

- 3ft USB cable, bracket set

OPTIONS

- PS-504 5V DC power adapter, RK 4PT 19" rack adapter, IR Cables—C A35M/2IRE-10, C-A35M/IRR-3, C-AS35M/AS35F-50, CA35M/IRE-10, bulk cable for serial control—BC-1T-300M, Serial Cables-C-D9F/OPEN-3/6/10/15/25/35/50, BC-1T-300M bulk cable

PRODUCT DIMENSION

- 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H

PRODUCT WEIGHT

- 0.1kg (0.2lbs) approx

SHIPPING DIMENSION

- 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT

- 0.3kg (0.6lbs) approx