

Kramer FC-7 2-Port Multi-Function GPIO/Relay Control Gateway

PORTS

- 2 GPIO/relay multi-function ports on 3-pin terminal blocks each selectable as either 2 GPI/O or 1 Relay ports, 1 Ethernet on an RJ-45 female connector, 1 mini USB connector for local services

MAXIMUM SIMULTANEOUS IP-CLIENT CONNECTIONS

- 40

POWER CONSUMPTION

- 5V DC, 370mA

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

COOLING

- Convection

ENCLOSURE TYPE

- Pico Tools, aluminum

VIBRATION

- ISTA 1A in carton (International Safe Transit Association)

SAFETY REGULATORY COMPLIANCE

- CE

ENVIRONMENTAL REGULATORY COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

INCLUDED ACCESSORIES

- 3ft USB cable, bracket set

PRODUCT DIMENSION

- 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H

SHIPPING DIMENSION

- 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H