

# Kramer FC-7P 2-Port Multi-Function GPIO/Relay PoE Control Gateway

## PORTS

- 2 GPIO/relay multi-function ports on 3-pin terminal blocks each selectable as either 2 GPI/O or 2 relay ports, 1 LAN on an RJ-45 female connector, 1 mini USB connector for local services

## MAXIMUM SIMULTANEOUS IP-CLIENT CONNECTIONS

- 40

## POWER CONSUMPTION

- 5V DC, xxmA

## OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

## STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

## HUMIDITY

- 10% to 90%, RHL non-condensing

## COOLING

- Convection

## ENCLOSURE TYPE

- Tools, aluminum

## RACK MOUNT

- With optional rack adapter

## VIBRATION

- ISTA 1A in carton (International Safe Transit Association)

## SAFETY REGULATORY COMPLIANCE

- CE

## ENVIRONMENTAL REGULATOR COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

## INCLUDED ACCESSORIES

- 3ft USB cable, bracket set

## PRODUCT DIMENSION

- 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H

## PRODUCT WEIGHT

- 0.2kg (0.4lbs) approx

## SHIPPING DIMENSION

- 23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50" ) W, D, H

## SHIPPING WEIGHT

- 0.8kg (1.8lbs) approx