



KDS-DEC6

4K60 4:2:0 HDCP 2.2 Video Decoder

| HDMI | Ethernet - RJ-45 | 4K/60 UHD (4:2:0)



The KDSDEC6 decoder provides streaming over an IP network that carries 4K@60Hz (4:2:0) video, audio, IR, RS232, USB over IP with HDCP 2.2 in unicast (onetoone) or multicast (manytomany) configurations

FEATURES

Video Support - HDMI 4K@60Hz (4:2:0)

Audio Support - HDMI/line in, 7.1 PCM, Dolby TrueHD, and DTSHD Master audio

Virtualization - IR, USB, RS232 over IP

Network - Switch 1G multicast IGMP snooping managed layer 2

Power - PoE or external power supply

Control - Kramer Network, Web UI, API

HDCP - 2.2 compliance

Video Effects - PIP, video wall



KRAMER

TECHNICAL SPECIFICATIONS

Inputs:	1 Ethernet (LAN/PoE) on an RJ45 connector, 1 IR on 3.5mm mini jacks (Rx)
Outputs:	1 HDMI connector, 2 left and right unbalanced stereo audio on RCA connectors, 1 RS232 on terminal block connectors, 2 USB (type A) ports, 1 IR on 3.5mm mini jacks (Tx), 1 Ethernet on an RJ45 connector (daisychain LAN)
Network:	10M/100M/1000M
Network Switch:	1G multicast, IGMP snooping nonblocking, Layer 2
Streaming:	Unicast and multicast through RTSP (Real Time Streaming Protocol)
Controls:	Reset button, up and down channel buttons, channel 7 segment display, STATUS, LINK and ON LEDs
IR:	Wideband 20kHz~60kHz bidirectional IR transmission
Management:	API, Kramer Control, Kramer AV services (powered by Kramer Network)
Video Encoding/Decoding:	Compression standard MJPEG
HDCP:	HDCP 2.2
PRODUCT DIMENSION:	19.00cm x 10.30cm x 2.30cm (7.48" x 4.06" x 0.91") W, D, H
PRODUCT WEIGHT:	0.6kg (1.2lbs) approx
SHIPPING DIMENSION:	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H
SHIPPING WEIGHT:	0.8kg (1.7lbs) approx
Scaling and Cropping:	Built in scaling and cropping for flexible display of source content on the decoder output
Bit Rates:	4K peak: 850Mbps, 4K average: 350Mbps, 1080p average: 250Mbps
Resolution:	4096x2160@60Hz, 3840x2160@60Hz, 1920x1200@60Hz, 1920x1080@60Hz, 1864x1050@60Hz, 1856x1392@60Hz, 1792x1344@60Hz, 1728x1080@60Hz, 1704x960@60Hz, 1680x1050@60Hz, 1600x1200@60Hz, 1600x1050@60Hz, 1600x900@60Hz, 1536x960@60Hz, 1440x900@60Hz, 1440x576@60Hz, 1440x480@60Hz, 1400x1050@60Hz, 1366x768@60Hz, 1360x768@60Hz, 1280x1024@60Hz, 1280x960@60Hz, 1280x800@60Hz, 1280x768@60Hz, 1280x720@60Hz, 1224x768@60Hz, 1152x864@60Hz, 1152x720@60Hz, 1024x768@60Hz, 1064x600@60Hz, 1024x384@60Hz, 960x600@60Hz, 848x480@60Hz, 800x600@60Hz, 768x480@60Hz, 720x576@60Hz, 720x480@60Hz, and 640x480@60Hz, 640x400@60Hz, 640x350@60Hz
Audio Encoding/Decoding:	Compression standard (analog in/out): AACLC
Channels (HDMI embedded Audio):	PCM 2, 5.1, 7.1 Channel, Dolby Digital 5.1 Channel, Dolby Digital Plus, Dolby Digital TrueHD, DTS 5.1 Channel, DTSES, DTSHD High Resolution, DTSHD Master Audio
Power Options:	PoE, external PS
Power Consumption:	48V DC, 370mA max
Operating Temperature:	0° to +40°C (32° to 104°F)
Storage Temperature:	40° to +70°C (40° to 158°F)
Humidity:	10% to 90%, RHL noncondensing
Options:	IR cable (PN: 3500900617), external DC power supply (PN: 100800070)

