

Kramer NT-52P 2-Port Universal I/O PoE Control Gateway

PORTS

- 2 RS232/IR universal I/O ports on 3pin terminal blocks each selectable as one of:
- 1 bidirectional RS232 serial port
- 1 crossed bidirectional RS232 serial port
- 1 bidirectional RS485 serial port
- 2 IR emitter ports
- 2 GPI/O ports
- 2 relay ports,
- 1 LAN on an RJ45 female connector,
- 1 builtin IR sensor for IR learning,
- 1 mini USB connector for local services

SUPPORTED SERIAL PORT BAUD RATES

- 1200, 2400, 4800, 9600, 19200, 38400, 57600, 15200bps

RS-232 COMMUNICATION

- Transparent up to 115200bps

IR EMITTER CABLE RANGE

- 80m (260ft)

SUPPORTED IR OUTPUT FREQUENCIES

- 20kHz to 1.2MHz

SUPPORTED IR INPUT FREQUENCIES

- 20kHz to 60kHz

MAXIMUM DATA HANDLING OF DEVICE

- Up to 150kbps (summed on all ports, see Section 7.1)

MAXIMUM SIMULTANEOUS IP-CLIENT CONNECTIONS

- 40

POWER CONSUMPTION

- 12V DC, 200mA

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- 40° to +70°C (40° to 158°F)

HUMIDITY

- 10% to 90%, RHL noncondensing

COOLING

- Convection

ENCLOSURE TYPE

- Tools, aluminum

RACK MOUNT

- With optional RK3T rack adapter

VIBRATION

- ISTA 1A in carton (International Safe Transit Association)

SAFETY REGULATORY COMPLIANCE

- CE

ENVIRONMENTAL REGULATOR COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

INCLUDED ACCESSORIES

- 3ft USB cable, bracket set

PRODUCT DIMENSION

- 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT

- 0.2kg (0.4lbs) approx

SHIPPING DIMENSION

- 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT

- 0.8kg (1.8lbs) approx