

Kramer PA-120Z Power Amplifier (1x120W 70V/100V and 2x60W 8 Ohm)

INPUTS

- 1 unbalanced stereo on a 3.5mm connector
- 1 balanced stereo +4dBu/10kΩ on a 5 pin terminal block

OUTPUTS

- 1 balanced stereo line level on a 5-pin terminal block
- 1 stereo or 1 mono speaker output on a 4 pin large terminal block

INPUT SENSITIVITY

- Attains full power @ 0.3V (-10dBV)

OUTPUT POWER

- 2 x 60W @ 4Ω or 8Ω
- 1 x 120W @ 70V or 100V

AMPLIFIER TYPE

- Class D

MAXIMUM VOLTAGE GAIN

- 26dB SE / 32dB BTL

DYNAMIC RANGE

- 119dB

FREQUENCY RESPONSE

- 20Hz to 20kHz @ +/-1dB

S/N RATIO

- 80dB — 10dBV, 20 Hz — 20 kHz

CONTROLS

- Screw trimmer amplifier attenuator, IP and RS-232

AUDIO THD + NOISE

- THD+N (1kHz @ 1W) 0.003 %

AUDIO 2ND HARMONIC

- 0.08% @ 75W RMS @ 4Ω 6.67kHz

POWER SOURCE

- Universal mains operational voltage 85VAC — 265VAC

TOTAL SYSTEM EFFICIENCY

- 89.2%

INCLUDED ACCESSORIES

- Power cord

OPTIONS

- RK-1 rack adapter

PRODUCT DIMENSION

- 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H

SHIPPING DIMENSION

- 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H