

Datavideo HS-1600T-3C140TM HD/SD HDBaseT Portable Video Streaming Studio Kit

Model Name	HS-1600T
Product Name	4-Channel HD/SD HDBaseT Portable Video Streaming Studio
Video Standard	HD & SD
Video Format	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i/p 50Hz 480i/p 59.94Hz
Input Routable / Crosspoint	N/A
Video Input	3 x HDBaseT 1 x HDMI
Computer Graphic Interface	1 via HDMI
Down-converted output	Yes
Video output	3x HDMI PGM 1x STREAM (RJ-45)
Audio input	2x Balanced XLR 1x Stereo RCA (L/R) De-embedded Digital Audio
Audio output	1x Stereo headphone
Embedded audio support	2 ch Audio embedded
Audio Delay Calibration	N/A
A+V switching	N/A
USK	1x USK support Lumakey
DSK	N/A
Picture in Picture	1
Logo Insertion	N/A
Built-in Audio Mixer	Yes
Built-in Monitor Display	17.3" HD TFT LED backlit, 1920x1080 pix
Built-in Intercom & Tally	N/A
Streaming Video Encode	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
Streaming Audio Encode	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
Streaming Protocol	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP (Publish)
Streaming Control	Web browser UI for configuration and control Socket commands
Recording file system	FAT, exFAT, NTFS
Recording file format	MP4
Recording Setting Control	Web UI for system configuration and control
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	17.2 Lbs (7.8 Kg), Reinforce Plastic Case
Accessory	CB-60/61/62

TLM-700K

Product Name	T 4K LCD Monitor
Screen	7' TFT LCD
Chassis	Camera Mount
Resolution	1920x1200
Viewing Angle	(H) +85/-85 (V) +85/-85
Luminance/Contrast	450cd/m2 1000:1
Video Inputs	1x HDMI (1.4b), HDCP 1.4
Loop Through	1x HDMI (1.4b)
Supported Input Resolutions	4096x2160p (24Hz). 3840x2160p (23/24/25/29/30HZ), 2048x1080p (50/59.94/60HZ). 1080p (23.98/24/25/29.97/30/50/59.94/60HZ). 1080i (50/59.94/60HZ). 720p (23.98/24/25/29.97/30/50/59.94/60HZ). 576i (50Hz). 576p (50Hz). 480i (59.94/60HZ). 480p (59.94/60HZ)
Aspect Ratio	16:9
Tally LED	N/A
	Embedded Audio (48KHz sampling) Analog Stereo

Audio In/Out	(Phone Jack). Speaker x1 (2W)
Special Features	Focus assist (peaking). False Color. Histogram. Exposure. Pixel to Pixel Zoom. Underscan. Check Field(blue-only mode, monochrome mode)
Power	DC 12 V. 12W