

Smartavi LDX-2PS Dual DVI-D/USB1.1/Dual RS232 over CAT5/5e/6 Extender (Transmitter/Receiver) Kit

| VIDEO | |
|-----------------------|-------------------------------------------------------------|
| Format | DVI-D |
| Maximum Pixel Clock | 165 MHz |
| Input Interface (TX) | (2) DVI-D 29-pin female |
| Output Interface (RX) | (2) DVI-D 29-pin female |
| Resolution | Up to 1920 x 1200 @ 60Hz AND Up to 4K/2K (3840x2160) @ 30Hz |
| DDC | 5 volts p-p (TTL) |
| Input Equalization | Automatic |
| Input Cable Length | Up to 20 ft. |
| Output Cable Length | Up to 20 ft. |
| RS-232 | |
| Input Interface (TX) | (2) DB9 (Female) |
| Output Interface (RX) | (2) DB9 (Female) |
| Speed | @ 115 Kbps |
| IR | |
| Input Interface (TX) | (1) 3.5 mm (Female) |
| Output Interface (RX) | (1) 3.5 mm (Female) |
| Frequency Response | 30KHz to 80KHz |
| USB | |
| Input Interface (TX) | (1) USB Type B (Female) |
| Output Interface (RX) | (2) USB Type A (Female) |
| Signal Type | OHCI/VHCI (USB 1.1) |
| OTHER | |
| Power | External 100-240 VAC/5VDC3A @20W |
| Dimensions | 5.125 in W x 1 in H x 3.625 in D |
| Weight | 1 lb |
| Operating Temp. | 0-55 °C (32-131°F) |
| Storage Temp. | -20-85 °C (-4-185 °F) |
| Humidity | Up to 95% |