

Kramer VIA-COLLAGE Bundle VIA Collage Unit Bundled with 4 VIA Pad Units

VIA-COLLAGE Bundle - VIA Collage Unit Bundled with 4 VIA Pad Units

VIA Collage

VIA Collage is a wireless presentation and collaboration solution that makes it easier to get actual work done during meetings. With any laptop or mobile device, users can view, edit and comment on documents in real time, share files and chat with individuals or multiple participants simultaneously. The award-winning VIA Collage is the only wireless solution in the market that can show six user screens on a single main display and 12 on two displays. Users can also view the main display on their device. VIA Collage includes iOS mirroring. VIA Collage supports 3rd party conferencing and office apps, such as Microsoft Office®, Skype®, GotoMeeting®, Lync®, and WebEx®. The solution is ideal for any size meeting room or classroom.

- Wireless Connection - Connect wirelessly with your own device. No dongle needed.
- iOS Mirroring - Show any content from your iOS device on the main display.
- Multimedia - Share uninterrupted full HD wireless video streaming (up to 1080p60), MP3 files and photos.
- Cloud-Based - Drag and drop files to the Cloud to share instantly with other users.
- Start Collaboration - Click to collaborate through a common display. Multiple users can edit and control what's happening on the main display at the same time.
- File Sharing - Share files with one or several participants.
- Whiteboard - Annotate, illustrate and edit shared documents with any regular or touch-panel device.
- Enable Control - Give a participant control over a presenter's MAC® or PC laptop.
- Chat - Send an instant message to another user.
- Web Browser - Open any browser to display content from a Web site.
- View Main Display - View the main display on your own device.
- Third-Party Apps - Support for office and conferencing applications, such as Microsoft Office®, Skype®, GotoMeeting®, Lync®, and WebEx®.
- HDMI Input - Connect any HDMI source (camera, DVD, Blu-ray™) and present it on the main display.
- Multilingual Support - Experience VIA in your language.

Features:

- Login using conventional Wi-Fi or LAN connections
- Supports Windows laptops and MAC®, as well as iOS and Android mobile operating systems
- Easy to use, simple and intuitive user interface
- High quality video streaming, supports full HD 1080p/60
- Up to six participant screens can be displayed simultaneously, or 12 – using dual screen mode
- Powerful security features: user authentication, 1024-bit encryption, dynamic room code
- Audio - U

Specifications:

INPUTS:	1 HDMI, 4 USB 3.0, 1 USB 2.0, 1 LAN on a RJ-45 connector (1 iAMT8.0 on an RJ-45 connector, for future use), 1 unbalanced stereo audio (line or mic).
GRAPHIC OUTPUTS:	1 HDMI, 1 DisplayPort.
PORT:	1 RS-232 on a 9-pin D-sub connector for projector control (for future use).
AUDIO OUTPUT:	Analog line out, embedded HDMI.
PROCESSOR:	2.9GHz quad core, low power consumption.
MAIN MEMORY:	4GB, high speed.
STORAGE:	64GB, solid-state drive.
LAN:	Dual gigabit LAN port, 10/100/1000/auto, one with iAMT 8.0.
AUDIO:	Integrated high definition audio 5.1 channel.
POWER SUPPLY:	120W power adapter (19V, 6A).
INPUT VOLTAGE:	100V~220V AC, 50/60Hz, auto sensing.
NET WEIGHT:	2.3kg (5.1lbs).
DIMENSIONS:	29.7cm x 5.6cm x 21.1cm (11.7" x 2.2" x 8.3") W, D, H.
INCLUDED ACCESSORIES:	3 power cords (US, EU, UK), DP to HDMI Kramer adapter.
OPTIONAL ACCESSORY:	2U rack adapter.

Package Includes:

- VIA Collage Collaboration Device
- Power supply (19V DC) with power cords

- Quick Start Guide
- DP to HDMI Adapter

VIA Pad

The VIA Pad is an optional step-in/step-out touch pad accessory for the VIA product line. It allows the user to easily share his/her laptop screen on the VIA equipped meeting room display.

Features

- Easy Plug and Play Connection - Over standard USB.
- Status LED Ring - Indicates active, standby, pause and do not disturb status.
- PC System Compatibility - Mac and Windows 7/8/10.
- VIA Compatibility - Ver 1.8 and onwards.

Specifications:

POWER CONSUMPTION:	5V DC, 55mA max.
STANDARDS COMPLIANCE:	CE, FCC.
DIMENSIONS:	8.03cm x 7cm x 1.4cm (3.16" x 2.76" x 0.55") W, D, H.
SHIPPING DIMENSIONS:	32cm x 10.5cm x 2.5cm (12.6" x 4.14" x 1.0") W, D, H.