

TVlogic LVM-170A 17 inch Full HD 1920x1080 multi-purpose 3G-SDI/DVI/HDMI LCD Monitor

LCD	Size	17.3"
	Resolution	1920 X 1080(16:9)
	Pixel Pitch	0.199(H) X0.199(V) mm
	Color Depth	16.7M (8bit-D)
	Viewing Angle	H: 178 degrees/V: 178 degrees
	Luminance of white	300 cd/m ² (Center)
	Contrast Ratio	700:1
	Display Area	381(H) X214(V) mm
Input Connector	1 X DVI-I	DVI-IN
	1 XBNC	CVBS Input
	2 XBNC	SDI Channel Input
	1 XHDMI	HDMI Input
Output	1 XBNC	CVBS Output
	1XBNC	SDI Channel (Active Through Out)
Input Signal	Analog	Composite
	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	DVI	VESA/IBM Modes
	HDMI	480i / 480p / 720p / 1080i VESA/IBM Modes
Analog Input Spec	Composite	I.OVpp (with Sync)
SDI Input Signal Formats	SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i(60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-260M	1035i (60/59.94)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
Audio In		Embedded Audio / Analog Stereo (Phone Jack)
Audio Out		Analog Stereo (Phone Jack), Speaker (Mixed Mono)
Power		AC 100~240V (50~60Hz)
Power Consumption (Approx.)		60 Watts(Max. 5A)
Operating Temperature		0°C to 40°C (32°F to 104°F)
Storage Temperature		-20°C to 60°C (-4°F to 140°F)
Main Body Dimensions (mm/inch)		421.5 x 264 x 74.1 (16.59 x 10.39 x 2.92)
Main Body Dimensions with stand (mm/inch)		483.5 x 310.3 x 137.5 (19.04 x 12.22 x 5.41)
Box Dimensions (mm/inch)		555 X 450 X 280 (21.85 X 17.72 X 11.02)
Weight		4.2kg/9.26lbs
Basic Accessories		AC Power Cord, Stand, USB Cover
Optional Accessories		Rack Mountable Kit, Acrylic Filter, Sun Hood, Carrying Case, V-mount, G-mount