

## TVlogic LVM-171A 16.5 inch Full HD 1920x1080 multi-purpose 3G-SDI/DVI/HDMI Super IPS LCD Monitor

LCD	Size	16.5"
	Resolution	1920X1080 (16:9)
	Pixel Pitch	0.1905(H) X0.1905(V) mm
	Color Depth	1.07B (8bit+2bit FRC)
	Viewing Angle	H : 178degrees/V: 178degrees
	Luminance of white	450 cd/m <sup>2</sup> (Center)
	Contrast Ratio	1500:1
	Display Area	365.8(H) X205.7(V) mm
Input Connector	1 X DVI-I	DVI-IN
	1 XBNC	CVBS Input
	2 XBNC	SDI Channel Input
	1 XHDMI	HDMI Input
Output	1 XBNC	CVBS Output
	1 XBNC	SDI Channel (Active Through Out)
Input Signal	Analog	Composite
	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	DVI	VESA/IBM Modes
	HDMI	480i /480p / 720p /1080i VESA/IBM Modes
Analog Input S pec	Composite	1.0Vpp (with Sync)
SDI Input Signal Formats	SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i(60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-260M	1035i (60/59.94)
SMPTE-125M	480i (59.94)	
ITU-R BT.656	576i (50)	
Audio In	Embedded Audio / Analog Stereo (Phone Jack)	
Audio Out	Analog Stereo (Phone Jack), Speaker (Mixed Mono)	
Power	AC 100-240V (50~60Hz)	
Power Consumption (Approx.)	32 Watts	
Operating Temperature	0°C to 40°C (32°F to 104°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Main Body Dimensions (mm/inch)	445 X 264 X 78.4 (17.52 X 10.39 X 3.09)	
Main Body Dimensions with stand (mm/inch)	492.2 X 288.8 X137.5 (19.38 X11.37 X 5.41)	
Box Dimensions (mm/inch)	555 X 450 X 280 (21.85 X 17.72 X 11.02)	
Weight	6.8kg / 14.99lbs	
Basic Accessories	AC Power Cord, Stand, USB Cover	
Optional Accessories	Rack Mountable Kit, Acrylic Filter, Sun Hood, Carrying Case, V-mount, G-mount	