

Nexto DI NSB-25 Modular Memory Card Backup System for 4K and UHD

Weight	1.5 kg / 3.3 lb (w/o drive & memory module installed)
Dimension	176 x 103 x 96 (mm) / 7 x 4 x 3.8 (inches)
LCD	5" Color TFT LCD: 800*480, 24-bit color
Memory card Support	Built in slot CF, SD (SDHC/SDXC with UHS-1 support) 1 ea of exchangeable memory module slot for Bridge Memory Module
Backup Storage	Two removable hard drive slot for Bridge Pellet (sold separately) One USB3.0 Host port for any USB3.0 drive
File System	Memory card FAT32 / exFAT / UDF / HFS+ Bridge pellet (Internal drive) exFAT USB external drive exFAT
Video Support	Normal Playback H.264 420, MPEG2 420, AVCHD, MPEG2 422 35M, XAVC 420, DV QUASI Playback MPEG 422 50M, ProRes 2K Preview AVC-Intra, XAVC 422, DNxHD, 4K footage Supported Video File Format .mxf / .mov / .mp4 / .mts / .dv / (.avi)
Video Out	Built in LCD or an external monitor interface
Audio Support	LPCM audio
Audio Out	Built in speaker (mono). Built in audio jack.
Photo Support	JPEG (.jpg) / Canon RAW (.cr2) / FujiFilm RAW (.raf) / Leica RAW (.dng / .rw1) / Nikon RAW (.nef) / Olympus RAW (.orf) / Panasonic RAW (.rw2) / Pentax RAW (.dng / .pef) / Samsung RAW (.srw) / Sony RAW(.arw)
Battery	3.7V 13200mAH Rechargeable Li-Poly battery Rechargeable via AC power adapter (6 hrs), USB cable (12 hrs), car charger cable. Use 3 hours (with two Bridge Pellet connected) with single charge. Copy 1TB to two drive simultaneous with single charge.
External Device Support	USB external drive / RAID
Computer I/F	USB 3.0 : 5Gbit/sec
OS Compatibility	Windows XP(SP2) / VISTA /7/8/10 (Windows XP requires exFAT patch update) MAC OS 10.6.5 or later, Linux 2.4.18 or later
Power	Recommended : DC 12V/2A Operational range: DC ±6~25V, external diameter 3.5mm, internal diameter 1.3mm Operated by USB bus power during the computer connection