

# Nexto DI NVS2801-Plus-2TB Portable All in One Backup Storage with 2TB SSD

Weight	430g / 0.95lb (with hard drive)
Dimension	154 x 91 x 33 (mm) /6x3.6x1.3 (inches)
LCD	2.4-inch Color TFT LCD: 320*240, 64K color
Memory card Support	<p><b>Built in slot</b> SxS(Pro/Pro+/-1), CFast(1.1 &amp;2.0), SD(SDHC/SDXC with UHS support)</p> <p><b>Optional card adapter</b> P2</p> <p><b>USB Card Reader</b> AJA PAK, AXSM, CF, express P2, RED</p>
Storage	<p><b>Internal drive</b> 2.5" SATA hard drive with 9.5mm and less height.</p> <p><b>External drive</b> One USB3.0 host port for any USB3.0 drive</p>
File System	<p><b>Internal drive</b> exFAT</p> <p><b>Memory card</b> FAT16/32, exFAT, UDF, HFS+ USB</p> <p><b>External drive</b> exFAT</p>
Video Preview	XAVC 4K, XAVC 2K, AVC Ultra 4K, AVC Ultra 2K, XF-AVC 4K, XF-AVC 2K, H.264 (.mov), AVC HD 2K, PRORES 4K, PRORES 2K, DNxHD 2K, MPEG 444/422/420, DVCPRO HD
Internal Battery	<p>Rechargeable Li-Poly battery, 3.7V4400mAH</p> <p>Operating time after full charge : 120min</p> <p>Rechargeable via AC adapter(5hrs), USB cable(9hrs)</p>
Computer I/F	USB 3.0 : SGbit/sec
OS Compatibility	<p>Windows XP / VISTA /7/8/10 (Windows XP requires exFAT patch update)</p> <p>MAC OS 10.6.5 or later, Linux 2.4.18 or later</p>
Power	<p>Recommended : DC 12V/2A</p> <p>Operational range: DC ±6~25V, external diameter 3.5■, internal diameter 1.3■</p> <p>Operated by USB bus power during the computer connection</p>