

KVM-TEC MVX2-FR Masterline Dual DVI/VGA/USB2.0/Audio Fiber Extender (Receiver)

| | | |
|-----------------------|---|---|
| | | MVX2-F Remote/CON |
| Interfaces | Video: | 2 x DVI-D out |
| | USB 2.0: | 4 x USB-A (devices) |
| | Audio: | 1 x 3,5mm jack plug (Line In) 1 x 3,5mm jack plug (Speaker) |
| | RS232: (optional) | 1 x D-Sub connector(male) |
| Video | Signal type: Resolution (digital): Resolution (analog): (opt.) Color mode: | DVI-D max. 1920x1200 @60Hz max. 1920x1200 @60Hz 24bit |
| Audio (Optional) | Type: Bandwidth: | |
| USB | Specification: Type: Rate: | |
| RS232 (optional) | Type: Rate: Signals: | |
| Casing | Material: Dimension (W x H x D): Weight: | anodized aluminum 198 x 40 x 103.5 mm (7,79x1,57x4,07") 582g (20,5 oz) |
| Power supply | Type: | external power supply 12VDC 2A |
| Power input | Operation: | 12W without USB devices |
| Operation environment | Temperature: Humidity: | 0 to +45 ■C (32 to 133 ■F) < 90%, non-condensing |
| Storage enviroment | Temperature: Humidity: | -25 to 80 ■C (-13 to 176 ■F) < 90%, non-condensing |
| Cooling | | Free air convection |
| MTBF | | 82.820 calculated hours approx.10 years |
| Conformity | | CE, FCC |
| Warranty | | 2 years (5 years opt) |
| Delivery including | Devices: | 1 x MVX2-F remote (CON) |
| | Power Supply: | 1 x power supply12V 2A (EU-plug) |
| | Cables: | |
| | SFP-Module: | 1 x SFP Module Multimode up to 500m(1640ft) (Optional with Single-Mode up to 20km/12 mi) |
| | Mounting: | Quickstart Manual |