

KVM-TEC SVX1L Smartline HDMI/DVI/USB 2.0 KVM Extender (Transmitter)

		SVX1 Local/CPU
Interfaces	Video:	1 x HDMI in (no HDCP) 1 x DVI-I out
	USB 2.0:	1 x USB-B to PC
Video	Signaltype: Resolution (digital): Colour mode:	DVI-I max. 1920x1200 @60Hz 24bit
USB	Specifikation: Type: Transmission rate:	USB 2.0 transparent max. 480 Mbit/s mass storage devices ad camera optional
Casing	Material: Dimension (W x H x D): Weight	anodized aluminum 97.5 x 40 x 103.5 mm (3,83x1,57x4,08") 302g (10,06oz.)
Power supply	Type:	External power supply 12VDC 1A
Power input	Operation:	6W
Operation environment	Temperature: Humidity:	Obis +45 ■C (32 bis 133 ■F) < 90%, non condensing
Lagertemperatur	Temperature: Humidity:	-25 bis 80 ■C (-13 bis 176 ■F) < 90%, non-condensing
Cooling		Free air convection
MTBF		82.820 calculated hours approx. 10 years
Conformity		CE, FCC
Warranty		2 years (5 years opt)
Delivery including	Devices:	1 x SVX1 local (CPU)
	Power supply:	1 x power supply 12V 1A (EU-plug)
	Cables:	1 x DVI - HDMI cable 1,8m (5,9ft) 1 x USB cable 1,8m (5,9 ft)
	Mounting:	4 x Rubber feet 4 x Mounting pads