

# NTI enviromux-ipcam-whnpt High-Definition Wireless/Wired Day/Night Pan/Tilt IP Camera

- View the camera from the ENVIROMUX web interface, camera web interface, included software, or with a compatible cell phone.
  - Control the camera using the camera web interface accessible from the ENVIROMUX web interface.
- With the E-2D/5D/16D, a triggered snapshot can be forwarded in alert e-mails or stored locally on a connected flash drive.
  - A snapshot can be triggered by any programmed event (motion detection, door open/close, glass break, smoke, liquid detection, etc.)
- Two-way audio with built-in microphone and built-in speakers. 3.5mm stereo audio port.
- IR night vision supports up to 32.8 ft (10 m).
- CMOS sensor
- Video codecs/Resolution:
  - H.264: 1280x720 up to 30 fps
  - MJPEG: 640x352 up to 30 fps
- Lens: 3.6 mm (0.14 in).
- Supports wireless 802.11b/g/n.
- Pan and tilt:
  - Pan: 355°
    - Speed range: 5 to 30°/sec
  - Tilt: 90°
    - Speed range: 5 to 50°/sec
- Built-in motion detection
  - Auto-patrol preset positions: 4.
  - Camera sends snapshots via email when motion is detected.
- Power:
  - Input: 100 to 240 VAC at 50 or 60 Hz, 0.2 A
  - Output: 5 VDC, 1A external power adapter
- 10/100 Mbps Ethernet port for wired connections.
- Requires Windows XP/7/8/10 or MAC OS 10.
- Operating temperature: 14 to 122°F (-10 to 50°C).
- Operating humidity: 0 to 95% non-condensing RH.
- Dimensions WxDxH: 3.43x4.25x3.9 in (87x108x99 mm).
- Compatible with the E-2D/5D/16D.
- Mounting base and mounting hardware included.
- Regulatory approvals: CE, RoHS.