

Barco R9023002 F22 1080 3000 lumens Ultra Wide High Brightness Projector

| Image Display | |
|------------------------|--|
| Display System | 1-Chip DLP |
| Native Resolution | 1920 x 1080 (Full HD) |
| Supported Resolutions | SXGA+ - 1400 x 1050 WUXGA - 1920 x 1200 |
| Max Brightness | 3000 Lumens |
| Uniformity | Not Specified by Manufacturer |
| Offset | Not Specified by Manufacturer |
| Aspect Ratio | Native: 16:10 Supported: 4:3 Supported: 16:9 |
| Contrast Ratio | 2500:1 |
| Dynamic Contrast Ratio | Not Specified by Manufacturer |
| DLP Link 3D | Not Specified by Manufacturer |
| Supported 3D Formats | Not Specified by Manufacturer |
| Color Wheel | 3-Segment (R, G, B) |
| Color Depth | Not Specified by Manufacturer |
| Scan | Horizontal: 15 - 150 Hz Vertical: 48 - 190 kHz |
| Lens | Not Specified by Manufacturer |
| Lens Shift | Not Specified by Manufacturer |
| Optical Zoom | Not Specified by Manufacturer |
| Throw Distance | Not Specified by Manufacturer |
| Throw Ratio | 0.74:1 |
| Projection Size | Not Specified by Manufacturer |

| Input/Output Connectors | |
|--------------------------------|--|
| Inputs/Outputs | 1 x DVI-D Video (Input) 1 x HDMI Control (Input) 1 x VGA (DE-15) Video (Input) 1 x HDMI Video (Input) 1 x Component (3RCA) Video (Input) 1 x S-Video (4-Pin DIN) Video (Input) 1 x Composite (BNC) Video (Input) 1 x Ethernet (RJ45) Control (Input/Output) 2 x Unspecified Signal (DE-9) Control (Input/Output) 1 x USB Control (Input/Output) 2 x 1/8" (3.5 mm) Mini Control (Input) 1 x 1/8" (3.5 mm) Mini Control (Input) |

| General | |
|--------------------|---|
| Light Source | Lamp (1 x UHP) |
| Color Temperature | Not Specified by Manufacturer |
| Lamp Power | 220 W |
| Expected Lamp Life | Medium Brightness: 2250 Hours Low Brightness: 3000 Hours |
| Fan Noise | Not Specified by Manufacturer |
| Security | Not Specified by Manufacturer |
| Menu Languages | Not Specified by Manufacturer |
| AC Input Power | 120 to 240 VAC, 50 / 60 Hz |
| Heat Dissipation | 1061 BTU |
| Power Consumption | Not Specified by Manufacturer |

| | |
|------------------------|---|
| Max Operating Altitude | Not Specified by Manufacturer |
| Temperature | Operating 50 to 104°F (10 to 40°C) Humidity: 20 - 80% Storage -4 to 140°F (-20 to 60°C) Humidity: 10 - 90% |
| Dimensions (W x H x D) | 10.9 x 3.7 x 9.2" / 278.0 x 94.0 x 234.0 mm |
| Weight | 6.4 lb / 2.9 kg |