

Barco R9023029 F22 SXGAplus Wide 2000 lumens VizSim Bright OptiLoc Projector

Image Display	
Display System	1-Chip DLP
Native Resolution	1400 x 1050 (SXGA+)
Supported Resolutions	Maximum: WUXGA - 1920 x 1200
Max Brightness	2000 Lumens
Aspect Ratio	Native: 4:3
Contrast Ratio	2500:1
Color Wheel	3-Segment (R, G, B)
Color Depth	10-Bit (1.07 Billion Colors)
Scan	Horizontal: 15 - 150 kHz Vertical: 48 - 190 Hz
Lens	f/2.6 (f = 19.7 mm)
Optical Zoom	None
Throw Ratio	1:1

Input/Output Connectors	
Inputs/Outputs	1 x HDMI Video (Input) 1 x DVI-I Video (Input) 1 x S-Video (4-Pin DIN) Video (Input) 1 x VGA (DE-15) Video (Input) 1 x Composite (RCA) Video (Input) 1 x Component (3RCA) Video (Input) 1 x 1/8" (3.5 mm) Mini Remote (Input) 1 x 12 V Trigger Control (Input) 1 x USB Type-B Female (Input) 1 x Ethernet (RJ45) Control (Input)

General	
Light Source	Lamp (1 x UHP)
Lamp Power	220 W
Expected Lamp Life	Low Brightness: 2250 Hours Low Brightness: 3000 Hours
AC Input Power	120 to 240 VAC, 50 / 60 Hz
Heat Dissipation	1061 BTU
Temperature	Operating 50 to 104°F (10 to 40°C) Humidity: 20 - 80% Storage -4 to 140°F (-20 to 60°C) Humidity: 10 - 90%
Dimensions (W x H x D)	10.9 x 3.7 x 9.2" / 278.0 x 94.0 x 234.0 mm
Weight	6.4 lb / 2.9 kg <i>approximately</i>