

## Barco R9023220 F50 1080 2600 lumens VizSim Bright Projector/No lens/Pearl White

| Image Display         |                               |
|-----------------------|-------------------------------|
| Native Resolution     | 1920 x 1080 (Full HD)         |
| Supported Resolutions | Full HD 1080p                 |
| Max Brightness        | 2600 Lumens                   |
| Uniformity            | >80%                          |
| Aspect Ratio          | Native: 16:9                  |
| Contrast Ratio        | 5300:1                        |
| DLP Link 3D           | Yes                           |
| Supported 3D Formats  | Not Specified by Manufacturer |
| Color Depth           | Not Specified by Manufacturer |

| Input/Output Connectors |  |
|-------------------------|--|
| Inputs/Outputs          | 1 x RS-232C (Unspecified Connector) Control (Input)<br>1 x Ethernet (RJ45) Control (Input)<br>1 x USB Control (Input)<br>2 x Composite (BNC) Control (Input)<br>1 x VGA (DE-15) Video (Input)<br>2 x DisplayPort Video (Input)<br>1 x DVI-D Video (Input)<br>1 x HDMI Video (Input)<br>1 x VGA (DE-15) Video (Input)<br>2 x 3G-SDI (BNC) Video (Input) |

| General                |   |
|------------------------|---|
| Light Source           | Lamp (1 x UHP)  |
| Lamp Power             | 350 W   |
| Expected Lamp Life     | Medium Brightness: 2000 Hours<br>Low Brightness: 2500 Hours   |
| AC Input Power         | 120 to 240 VAC, 50 / 60 Hz  |
| Heat Dissipation       | 1807 BTU  |
| Power Consumption      | Medium Brightness: <530 W   |
| Temperature            | <b>Operating</b><br>50 to 104°F (10 to 40°C)<br>Humidity: 20 - 80%<br><b>Storage</b><br>-4 to 140°F (-20 to 60°C)<br>Humidity: 10 - 90% |
| Dimensions (W x H x D) | 13.5 x 12.0 x 6.0" / 34.3 x 30.5 x 15.2 cm  |
| Weight                 | 16.5 lb / 7.5 kg  |