

Barco R9023268 F22 WUXGA Zoom 3000 lumens High Brightness (MKIII) Projector/White

| Image Display          |                                                    |
|------------------------|----------------------------------------------------|
| Display System         | 1-Chip DLP                                         |
| Native Resolution      | 1920 x 1200 (WUXGA)                                |
| Supported Resolutions  | SXGA+ - 1400 x 1050<br>Full HD 1080p - 1920 x 1080 |
| Max Brightness         | 3000 Lumens                                        |
| Uniformity             | Not Specified by Manufacturer                      |
| Offset                 | Not Specified by Manufacturer                      |
| Aspect Ratio           | Native: 16:10<br>Supported: 4:3<br>Supported: 16:9 |
| Contrast Ratio         | 2500:1                                             |
| Dynamic Contrast Ratio | Not Specified by Manufacturer                      |
| DLP Link 3D            | Not Specified by Manufacturer                      |
| Supported 3D Formats   | Not Specified by Manufacturer                      |
| Color Wheel            | 3-Segment (R, G, B)                                |
| Color Depth            | Not Specified by Manufacturer                      |
| Scan                   | Horizontal: 15 - 150 Hz<br>Vertical: 48 - 190 kHz  |
| Focus                  | Manual                                             |
| Lens                   | Not Specified by Manufacturer                      |
| Lens Shift             | Not Specified by Manufacturer                      |
| Optical Zoom           | Not Specified by Manufacturer                      |
| Throw Distance         | Not Specified by Manufacturer                      |
| Throw Ratio            | 0.92:1                                             |
| Projection Size        | Not Specified by Manufacturer                      |

| Input/Output Connectors |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inputs/Outputs          | 1 x DVI-D Video (Input)<br>1 x HDMI Control (Input)<br>1 x VGA (DE-15) Video (Input)<br>1 x HDMI Video (Input)<br>1 x Component (3RCA) Video (Input)<br>1 x S-Video (4-Pin DIN) Video (Input)<br>1 x Composite (BNC) Video (Input)<br>1 x Ethernet (RJ45) Control (Input/Output)<br>2 x Unspecified Signal (DE-9) Control (Input/Output)<br>1 x USB Control (Input/Output)<br>2 x 1/8" (3.5 mm) Mini Control (Input)<br>1 x 1/8" (3.5 mm) Mini Control (Input) |

| General            |                                                             |
|--------------------|-------------------------------------------------------------|
| Light Source       | Lamp (1 x UHP)                                              |
| Color Temperature  | Not Specified by Manufacturer                               |
| Lamp Power         | 220 W                                                       |
| Expected Lamp Life | Medium Brightness: 2250 Hours<br>Low Brightness: 3000 Hours |
| Fan Noise          | Not Specified by Manufacturer                               |
| Security           | Not Specified by Manufacturer                               |
| Menu Languages     | Not Specified by Manufacturer                               |
| AC Input Power     | 120 to 240 VAC, 50 / 60 Hz                                  |
| Heat Dissipation   | 1061 BTU                                                    |
|                    |                                                             |

|                        |                                                                                                                                         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Power Consumption      | Not Specified by Manufacturer                                                                                                           |
| Max Operating Altitude | Not Specified by Manufacturer                                                                                                           |
| Temperature            | <b>Operating</b><br>50 to 104°F (10 to 40°C)<br>Humidity: 20 - 80%<br><b>Storage</b><br>-4 to 140°F (-20 to 60°C)<br>Humidity: 10 - 90% |
| Dimensions (W x H x D) | 10.9 x 3.7 x 9.2" / 278.0 x 94.0 x 234.0 mm                                                                                             |
| Weight                 | 6.4 lb / 2.9 kg                                                                                                                         |