## Aten CL3800NW 1U Dual Rail 18.5in FHD LCD KVM Console (USB/HDMI/DVI/VGA)

	To 2000 W	
Function	CL3800NW	
Computer Connections		
Direct		
Console Selection	Hotkey	
Connectors		
External Console Ports	1 x HDMI Female 1 x DVI-D Female (White) 1 x HDB-15 Female (Blue) 2 x USB Type A Female 1 x 3.5mm Audio Jack Female (Green)	
KVM Ports	1 x HDMI Female 1 x DVI-D Female (White) 1 x HDB-15 Male (Blue) 1 x USB Type B Female 1 x 3.5mm Audio Jack Female (Green)	
USB Port	1 x USB Type A Female	
Firmware Upgrade	1 x 3.5mm Audio Jack Female (Black)	
Power	1 x 3-prong AC Socket	
Switches		
Reset	1 x Semi-recessed Pushbutton	
Firmware Upgrade	1 x Slide	
Power	1 x Rocker	
LCD Power	1 x Pushbutton	
LCD Adjustment	4 x Pushbutton	
LEDs	T A T d S T D A C C C C C C C C C C C C C C C C C C	
1 x KVM Console (Dark Green)		
Power	1 x LCD (Orange)	
Lock	1 x NumLock (Green) 1 x CapsLock (Green) 1 x ScrollLock (Green)	
Video	·	
Input Video Resolution	1920 x 1200 @ 60 Hz, DDC2B	
Panel Spec		
LCD Module	18.5" TFT-LCD	
Resolution	1920 x 1080 @ 60 Hz	
Pixel Pitch	0.213 mm x 0.213 mm	
Response time	20 ms	
Viewing Angle	178° (H), 178° (V)	
Contrast Ratio	1000:1	
Support Color	16.77M colors	
Luminance	350 cd/m <sup>2</sup>	
Emulation	In a service	
Keyboard / Mouse	USB	
Maximum Input Power		
Rating	100-240V AC; 50-60Hz; 1A	
Power Consumption	AC110V:26.6W:140BTU AC220V:26.8W:141BTU	
Environmental		
Operating Temperature	0-40°C	
Storage Temperature	-20-60°C	
Humidity	0 - 80% RH, Non-condensing	
Physical Properties		
Housing	Metal	

Weight	9.61 kg ( 21.17 lb )
Dimensions (L x W x H)	48.06 x 51.42 x 4.28 cm (18.92 x 20.24 x 1.69 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.