

Aten RE24U100 24U RE Series Standing Network Rack (1191mm x 600mm x 1070mm)

| | |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Physical Properties | |
| Rack Height (U Spaces) | 24U |
| Type | Rack Enclosure |
| Package Contents | Build-Up(Default) Knock-Down(Special Requirement) |
| Mounting Hole Type | Square |
| Color | Black |
| Unit Dimensions(H*W*D) | 1191 x 600 x 1070 |
| Maximum Device Height | 1991 |
| Maximum Device Width | 600 |
| Maximum Device Depth | 1070 |
| Max/Min/Default Mounting | 975/270/840 |
| Maximum Mounting | 975 |
| Minimum Mounting | 270 |
| Default Mounting | 840 |
| Shipping DimensionsBuild-Up (H x W x D) | 1150 x 650 x 1341 |
| Shipping DimensionsKnock-Down (H x W x D) | Package1 : 1260 x 250 x 620 Package2 : 1170 x 210 x 160 Package3 : 1000 x 50 x 1010 |
| Shipping Weight | 100 |
| Unit weight | 80 |
| Weight capacity stationary | 1300 |
| Weight capacity dynamic | 1000 |
| Material | SPCC Cold Rolled Steel |
| Air permeability | 0.78 |
| Certifications | |
| Approvals | CE |
| Certifications | RoHS |
| Protection class | IP20 |
| Shipping | |
| Build-Up packing Unit volume (CBM) | 1.004 |
| Knock-Down packing Unit volume (CBM) | Package1 : 0.20 Package2 : 0.04 Package3 : 0.05 |
| Build-up package (20GP) | 18 |
| Build-up package (40GP) | 36 |
| Build-up package (40HQ) | 70 |
| Knock-Down package (20GP) | 60 |
| Knock-Down package (40GP) | 120 |
| Knock-Down package (40HQ) | 138 |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |