

Aten RE48U120 48U RE Series Standing Network Rack (2259mm x 600mm x 1200mm)

Physical Properties	
Rack Height (U Spaces)	48U
Type	Rack Enclosure
Package Contents	Build-Up(Default) Knock-Down(Special Requirement)
Mounting Hole Type	Square
Color	Black
Unit Dimensions(H*W*D)	2259 x 600 x 1200
Maximum Device Height	2259
Maximum Device Width	600
Maximum Device Depth	1200
Max/Min/Default Mounting	975/270/840
Maximum Mounting	975
Minimum Mounting	270
Default Mounting	840
Shipping DimensionsBuild-Up (H x W x D)	1350 x 650 x 2420
Shipping DimensionsKnock-Down (H x W x D)	Package1 : 2315 x 260 x 620 Package2 : 1130 x 80 x 985 Package3 : 2230 x 210 x 155
Shipping Weight	197
Unit weight	160
Weight capacity stationary	1300
Weight capacity dynamic	1000
Material	SPCC Cold Rolled Steel
Air permeability	0.78
Certifications	
Approvals	CE
Certifications	RoHS
Protection class	IP20
Shipping	
Build-Up packing Unit volume (CBM)	2.062
Knock-Down packing Unit volume (CBM)	Package1 : 0.37 Package2 : 0.09 Package3 : 0.07
Build-up package (20GP)	N.A.
Build-up package (40GP)	N.A.
Build-up package (40HQ)	26
Knock-Down package (20GP)	45
Knock-Down package (40GP)	93
Knock-Down package (40HQ)	109
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.